

# SPG All Weather SLIMLINE Keypad



Available with different technologies:

- 125kHz Prox QuadraKey
- 13.56MHz Mifare, Desfire, CPU



RS485 OSDP or Wiegand



Card reader function supported



Reverse power protection



Number pads use the latest Touch Sensor technology, with individual key backlighting



OSDP encryption supported



Design with End User Logo is available



LED Backlight



All weather-proof design with IP65 certificate



Front plate customisation and backlight design is available

## Technical Specifications

Typical Read Range	3-8 cm (Base on Different Technology)
Reader Standard Output	RS485 OSDP (Wiegand Optional)
Wiring Distance	150m (22 AWG with Shielded Cable)
Operating Voltage	10 - 15VDC
Operating Current	150mA (max)
Operating Temperature	-10°C to +70°C
Exterior Dimension	150 x 53 x 25mm
Case Material	PC + ABS
Standard Colour	Black
Operating Humidity	10% - 90%
Weight	180g



## Ordering Information

Part Number	Product Code	Description
300137	SD1-STXP-PRX-B	Slender Low-Frequency OSDP Keypad Reader. Can read HID Prox and EM card.
300138	SD1-STXP-MFRP-B	Slender Dual Tech OSDP Keypad Reader. Can read HIDProx, Mifare, Desifre and iClass card.
300134	SD1-STXPW-PRX-B	Slender Low-Frequency Wiegand Keypad Reader. Can read HID Prox and EM card.
300136	SD1-STXPW-MFRP-B	Slender Dual Tech Wiegand Keypad Reader. Can read HIDProx, Mifare, Desifre and iClass card.